

C2E

Wi-Fi Indoor PT Camera



3MP
Resolution



H.265



Type-C
Interface



Private
Mode



Pan and Tilt



Human
Detection



Two-Way Audio



Local &
Cloud Storage



Compatible With
ZSmart App



Brief Introduction

C2E is a premium pan & tilt smart indoor camera used for your home security. With C2E simple plug-in installation and smart core inside, this smart pan & tilt camera assists user to have peace of mind out of the busy life. The Wi-Fi supported pan-tilt smart indoor camera is compatible with all-in-one smart home app ZSmart, user can check the indoor situation anytime with high resolution live video and communicate instantly through two-way talk. Also, C2E offers user real-time notifications, motion detection and review recent activities with local or cloud storage.

C2E will be a wise choice for living room and kid's room, it creates a safer, smarter, and more convenient lives.

Features



3MP Resolution

Provide high-resolution live video



H.265

More storage space to save and less bandwidth to stream



Type-C Interface

Type-C port is more safe and convenient in use



Private Mode

Standby mode for privacy protection



Pan and Tilt

Rotate and set the camera's point of view via App



Human Detection

Filter out the false alarm objects and detect the human motion only



Two-Way Audio

Listen in or talk back and forth



Local & Cloud Storage

Store & review video footage

Specifications

Image	Image Sensor	1/3" CMOS Sensor
	Min. Illumination	0.1Lux / F2.0
	Resolution	3MP (2304*1296)
	Pan / Tilt	Pan 355° Tilt 66 °
	Focal Length	4mm lens
	Field of view	79.5° horizontal, 93.6° diagonal
	IR Light Distance	5m
Video	Video Compression	H.265
	Stream	Main stream (2304*1296) Sub stream (640*360)
	Frame Rate	50Hz: 15fps@1296p
	DNR	3D DNR
	WDR	DWDR
Audio	Audio Compression	G.711a/PCM/AAC
	Speaker & Microphone	Built-in
	Two Way Audio	Supported
Alarm	Motion Detection	Supported
	Human Detection	Supported
	Wireless Protocol	IEEE 802.11b/g/n (2.4GHz Wi-Fi)
	Data Security	End-to-end encryption WEP/WPA/WPA2
	Protocol	WebRTC
	Cloud Storage	Supported
General	Local Storage	Up to 256GB
	Power Supply	DC 5V
	Power Consumption	2W±10%
	Dimensions (W*L*D)	73*73*120 mm
	Operating Temperature	-15 C ~55 C
	Operating Humidity	<95%
	Certifications	CE

Applicable Scenarios



Living Room



Kid's Room

Dimensions (mm)

