



4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera

DH-H4A



Series Overview

The Hero Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. These highly sensitive cameras deliver crystal clear images and offer 360-degree monitoring without blind spots. Their powerful functions, such as human detection and auto tracking, not only assist with the accurate detection and continuous tracking of targets, but also reduce the occurrence of false alarms. It also features two-way talk, which allows you to freely communicate with your scene anytime, anywhere. Information is synchronously sent to your phone to keep you up-to-date. These cameras are widely used in small scenes such as shops and restaurants.



4MP

Clear images with sharp details



One Camera for 360° View

360° monitoring without blind spots



Human Detection

Focuses on what matters and reduces false alarms



Day&Night

Clear images even at night



Auto Tracking

Automatic tracking of targets



Two-way Talk

Communication anytime, anywhere



One-click Privacy Mode

Protects your privacy



H.265

Advanced H.265 compression technology




DMSS App

Easy to use



Micro SD Card

Low-cost storage



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.





Specifications

Camera

Image Sensor	1/3" CMOS
Max. Resolution	2560 (H) × 1440 (V)
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Illumination Distance	Up to 10 m (32.81 ft) (IR)
Illuminator On/Off Control	Auto
Illuminator Number	1 (IR LED)
Angle Adjustment	Pan: 0° to 355°; Tilt: -5° to +80°
Max. Aperture	3.6 mm: F2.0
Field of View	3.6 mm: H: 74°; V: 41°; D: 88°

Video & Audio

Video Compression	H.265
Video Frame Rate	Main stream: 2560 × 1440 @25 fps Sub stream: 640 × 480 @25 fps
Resolution	4M (2560 × 1440); VGA (640 × 480)
Video Bit Rate	H.265: 80 kbps–4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	OFF/ON
Image Rotation	0°/180°
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a


Network

Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n 2.4–2.4835 GHz, 2.4 G
Storage	Micro SD card (up to 256 GB)
Management Software	DMSS
Mobile Client	iOS;Android

General

Certifications	CE
Power Supply	5 VDC, 1A
Power Consumption	Basic: 1.8 W; Max. (video stream acquiring + IR + PTZ Rotation): 3.6 W
Operating Temperature	-10 °C to +45 °C (+14 °F to +113 °F)
Operating Humidity	≤ 95%
Casing Material	Plastic
Product Dimensions	φ77.8 mm × 108.1 mm (φ3.06" × 4.26")
Net Weight	204.2 g (0.45 lb)

What's in the box



× 1

Tools:

Installation Position Map×1
Mounting Platex1
Screw Package×1

Documents:

QR Codex1
Quick Start Guidex1
Legal and regulation information×1

Power:

Power Adapter×1
Power Cable×1

